

02-24-00

A

02/23/00
Jc658 U.S. PTOPlease type a plus sign (+) inside this box → ☐PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL <i>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</i>	Attorney Docket No.	FUJIP0108US
	First Inventor or Application Identifier	Maitani
	Title	IMAGE READER AND METHOD FOR ...
	Express Mail Label No.	EJ887878374US

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
-----------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------

1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing)	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 33] (preferred arrangement set forth below) - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure	6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 8]	
4. Oath or Declaration [Total Pages 4] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 16 completed) i. <input type="checkbox"/> <u>DELETION OF INVENTOR(S)</u> Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	

ACCOMPANYING APPLICATION PARTS	
7. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s))	
8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement of Power of Attorney (when there is an assignee)	<input type="checkbox"/> Attorney
9. <input type="checkbox"/> English Translation Document (if applicable)	
10. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449	<input type="checkbox"/> Copies of IDS Citations
11. <input checked="" type="checkbox"/> Preliminary Amendment	
12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)	
13. <input type="checkbox"/> * Small Entity Statement(s) filed in prior application, Status still proper and desired (PTO/SB/09-12)	<input type="checkbox"/> Statement filed in prior application, Status still proper and desired
14. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)	
15. <input checked="" type="checkbox"/> Other: <u>Certificate of Mailing</u>	

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a **CONTINUING APPLICATION**, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____ / _____

Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label _____ or <input checked="" type="checkbox"/> Correspondence address below (Insert Customer No. or Attach bar code label here)					
Name	Renner, Otto, Boisselle & Sklar, P.L.L.				
	Neil A. DuChes				
Address	1621 Euclid Avenue				
	19th Floor				
City	Cleveland	State	OH	Zip Code	44115
Country		Telephone	216-621-1113	Fax	216-621-6165

Name (Print/Type)	Neil A. DuChes	Registration No. (Attorney/Agent)	27,725
Signature	<i>Neil A. DuChes</i>	Date	2-23-00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

FUJIP0108US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Yoshifumi Maitani

Express Mail No.: EJ887878374US

Filed: February 23, 2000

For: IMAGE READER AND METHOD FOR CORRECTING THE QUANTITY OF LIGHT
OF THE READOUT LIGHT SOURCE

:
:
:
:
:
:
:

Art Unit:

Examiner:

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to commencing examination of the subject application, kindly enter the following amendment.

In The Claims:

Kindly amend claim 3 as follows:

3. (Amended) An image reader according to claim 1 [or 2], wherein said second standard white board is provided in the external region of both end portions of the document passing area with respect to the main scanning direction.

Kindly add claim 6 as follows:

6. An image reader according to claim 2, wherein said second standard white board is provided in the external region of both end portions of the document passing area with respect to the main scanning direction.


Remarks

Claim 3 has been amended to eliminate the multiple dependency of the claim. Claim 6 has been added. Claims 1-6 are in the application upon entry of this amendment. Entry of this amendment, and an early action indicating an allowance of the application is respectfully requested.

Respectfully submitted,

RENNER, OTTO, BOISSELLE & SKLAR, P.L.L.

By



Neil A. DuChez
Reg. No. 26,725

1621 Euclid Avenue
Nineteenth Floor
Cleveland, Ohio 44115
(216) 621-1113

SPECIFICATION

TITLE OF THE INVENTION

IMAGE READER AND METHOD FOR CORRECTING

5 THE QUANTITY OF LIGHT OF THE READOUT LIGHT SOURCE

BACKGROUND OF THE INVENTION

(1) Field of the Invention

10 The present invention relates to an image reader in a scanner, a unit scanner, a facsimile and the like installed in an image forming apparatus such as a digital copying machine and the like.

(2) Description of the Prior Art

15 In an image reader in a scanner, conventionally, shading correction is performed prior to the read operation of an original document image. Shading correction is intended for correcting the difference in sensitivity between pixels of a sensor (CCD) which reads an image based on the reflected light from the original document, and for correcting nonuniformity in the quantity of light of a light source comprising a
20 plurality of lamps.

The difference in sensitivity between pixels of the readout sensor and nonuniformity in the quantity of light of the light source cause difference in the image density, and
25 considerably decrease the reproducibility of the halftone

image.

With the shading correction, a standard white board serving as a basis of correction is first read, then an image data including the difference in sensitivity between each pixel of the CCD and nonuniformity in the quantity of light of the light source is obtained as the shading data, and the correction value with respect to the image data is determined for each pixel based on this data, to thereby determine the threshold for the white/black judgement.

On the other hand, models installed with a sheet-through type automatic document feeder are recently increasing, and such an image forming apparatus includes a document fixing mode in which an original document is put on an original table, and the document image is read while an optical system is moved along the original table, and a document moving mode in which the original document is read by the optical system located in place, while the original document is moved by means of the sheet-through type automatic document feeder. For example, in Japanese Patent Publication Hei 10 No. 200711, as shown in FIG. 1, a standard white board 82 is set between a moving document read section for reading an original document moved by the automatic document feeder 80 and a fixed document read section for reading a fixed document put on the original table 81, and the shading correction is performed in the document fixing mode and the document moving mode, using the standard

white board 82.

With this construction, however, at the time of continuous read in the document moving mode, problems described below occur.

5 In the case of the document fixing mode, the optical system 83 returns to the home position 84 of the optical system 83 every time when the optical system reads one sheet of document. Therefore, even in the case of continuous readout, white board 82 is irradiated to perform the shading correction
10 every time each document is read, hence the threshold of the white/black judgement does not shift.

However, in the case of the document moving mode, when the optical system 83 initiates read in of the first document, the optical system 83 moves from the home position 84 to the
15 moving document readout position, hence after the reflected light of the white board 82 has been read at the home position for the first document, and the shading correction has been performed, the correction must be performed always at the same correction value.

20 However, when dozens of documents are read continuously, for example, at the time of continuous copying, since the temperature of the light source increases, the quantity of light decreases, and with the same correction value as that of the first document, the threshold of the white/black
25 judgement shifts. As a result, such problems are caused that

the reproducibility of the halftone image decreases and that fogging is caused in the reproduced image.

In addition, even in the document moving mode, this problem can be solved by returning the optical system 83 to a predetermined home position 84 for each document to read the white board 82 and performing the shading correction, but such an operation not only conspicuously decreases the document read rate but also leads to a problem of precision of the document unit and complicated control.

Therefore, with the conventional image reader, in the document moving mode, the data for shading correction is not re-acquired during continuous readout.

SUMMARY OF THE INVENTION

The present invention is intended for solving the above described problems, and it is an object of the present invention to provide an image reader which can provide a high quality reproduced image by simply and accurately correcting the change in the quantity of light at the time of continuous readout in the document moving mode and improving the reproducibility of the halftone image, in an image reader which provides the document moving mode or the both document moving/document fixing modes, and to provide a method for correcting the quantity of light of the light source.

The present invention has the following construction

in order to attain the above described objects.

A first gist of the present invention is an image reader having a document moving mode in which an original document carried through a document passing area on an original table is read by a readout section, characterized in that:

a first standard white board being longer than the length of the document passing area with respect to the main scanning direction is provided outside the document passing area;

a second standard white board is provided in an external region of an end portion of the document passing area with respect to the main scanning direction;

a control section controls the readout section in such a way that, in the document moving mode, the readout section reads the first standard white board prior to the initiation of the document read to thereby perform the shading correction, and after the document read has been initiated, the readout section reads the moving document as well as the reflected light of the second standard white board, so as to correct the quantity of irradiation light of the readout section, based on the reflected light from the second standard white board.

A second gist of the present invention is an image reader having both of a document fixing mode in which a readout section moves to read an original document put in a document putting area on an original table, and a document moving mode in which

an original document carried through a document passing area on the original table is read by the readout section, characterized in that:

5 a first standard white board being longer than the length of the document putting area with respect to the main scanning direction is provided outside the document putting area;

10 a second standard white board is provided in an external region of an end portion of the document passing area with respect to the main scanning direction;

15 a control section controls the readout section in such a way that, in the document moving mode, readout means reads the first standard white board prior to the initiation of the document read to thereby perform the shading correction, and after the document read has been initiated, the readout section reads the moving document as well as the reflected light of the second standard white board, so as to correct the quantity of irradiation light of the readout section, based on the reflected light from the second standard white board.

20 A third gist of the present invention is an image reader according to the first or second gist, wherein the second standard white board is provided in the external region of both end portions in the main scanning direction in the document passing area.

25 A fourth gist of the present invention is a method for

correcting the quantity of light of a readout light source used in an image reader which irradiates an original document with the readout light source and reads the original document image based on the reflected light thereof, wherein

5 in a document moving mode in which the original document moves, the moving document image is read by using the readout light source, and the reflected light from a standard white board arranged outside a document passing area is also read; and

10 correction of the quantity of irradiation light of the readout light source is performed based on the reflected light from the standard white board.

 A fifth gist of the present invention is a method for correcting the quantity of light of a readout light source used
15 in an image reader which irradiates an original document with the readout light source and reads the original document image based on the reflected light thereof, wherein

 in a document moving mode in which the document moves,
 correction of the quantity of irradiation light of the
20 readout light source is performed by reading a first standard white board which is longer than the length in the main scanning direction of a document passing area, prior to the initiation of the document read;

 upon initiation of readout of the moving document, both
25 the document and a second standard white board arranged outside

the document passing area are read, by using the readout light source; and

correction of the quantity of irradiation light of the readout light source is performed based on the reflected light from the second white board.

According to the first or second gist, at the time of document moving mode, the control section performs shading correction based on the quantity of reflected light of the first standard white board arranged wider than the whole width of the document passing area or of the document putting area in the main scanning direction, for example, corrects the difference in sensitivity between pixels of the readout section and the nonuniformity in the quantity of light of the light source, immediately before starting read in of the moving document.

After performing the shading correction to thereby make the readout section the optimum state, the control section moves the readout section to a position where the moving document can be read, and read the quantity of reflected light of the second standard white board provided in a prescribed location at an end portion in the main scanning direction where the document does not pass through, every time predetermined moving documents are read. The control section detects the change in the quantity of irradiation light of the readout section based on the result, and corrects the quantity of

irradiation light of the readout section (readout light source).

Therefore, even if the quantity of irradiation light of the readout section decreases due to the continuous readout of the documents in the document moving mode, the quantity of irradiation light is maintained in the quantity of irradiation light after the shading correction performed by using the first standard white board, every time predetermined documents are read. Hence, the threshold of the white/black judgement determined by the shading correction does not shift, without reducing the read rate or without requiring complicated control, and high quality of reproduced document can be obtained.

According to the third gist, by arranging the second standard white board at both ends rather than at one end portion in the main scanning direction, more accurate correction of the quantity of light can be performed.

According to the fourth gist, in the document moving mode, the change in the quantity of light of the readout light source with lapse of time can be detected by providing the standard white board in a prescribed location in the external region of the end portion by utilizing the external region of the end portion in the main scanning direction in the area where the moving document does not pass through, and by reading the reflected light from this standard white board together with the reflected light from the moving document. Hence, it

becomes possible to correct the quantity of light of the readout light source to the predetermined quantity of light based on the change in the quantity of light.

5 Therefore, even in the document moving mode, correction of quantity of light becomes possible every time a document is read, without reducing the read rate and without requiring complicated control, and thus, the change in the quantity of light due to the change with lapse of time of the light source at the time of continuous readout can be properly corrected.

10 According to the fifth gist, in the document moving mode, for example, shading correction of nonuniformity in the quantity of light, difference in sensitivity of the pixel portion to be read is performed based on the reflected light of the first standard white board immediately before initiating readout of the document. Then, the light source moves to the
15 read position where the moving document is read, and even if the moving documents are continuously read to cause a change in the quantity of light due to the temperature increase of the light source, the change in the quantity of light of the readout light source can be detected and the change thereof
20 with lapse of time can be corrected by reading the reflected light which is irradiated by using the light source and reflected from the second standard white board provided in the region where the document does not pass through, for example,
25 in the external region of the end portion in the main scanning

direction of the passing document, every time predetermined documents are read.

Therefore, in the document moving mode, the change in the quantity of light of the light source can be corrected, while performing continuous read of documents, and the quantity of light of the document can be maintained in the quantity of light corrected by using the first standard white board. Hence, the threshold of the white/black judgement determined by the shading correction by using the first standard white board can be maintained, without interrupting continuous read for performing the shading correction, reducing the read rate or requiring complicated control, and high quality of reproduced document can be obtained.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front sectional view of an image forming apparatus having a conventional image reader.

FIG. 2 is a front sectional view of an image forming apparatus having an image reader according to an embodiment of the present invention.

FIG. 3 is a front sectional view of a scanner section 3 and a document automatic feeder 30 according to an embodiment of the present invention.

FIG. 4 is a top view of a scanner section 3 according to an embodiment of the present invention.

FIG. 5A and FIG. 5B are diagrams showing the light distribution characteristic (Fig. 5A) and the light distribution characteristic after continuous read (Fig. 5B) of a light source 3a for reading documents according to an embodiment of the present invention.

FIG. 6 is a block diagram of a control system of an image forming apparatus according to an embodiment of the present invention.

FIG. 7 is a flow chart of a readout operation in the document fixing mode of an image forming apparatus according to an embodiment of the present invention.

FIG. 8 is a flow chart of a readout operation in the document moving mode of an image forming apparatus according to an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As follows is a detailed description of an embodiment of the present invention with reference to the accompanying drawings. Here, an image forming apparatus installed with an image reader according to the present invention is exemplified.

As shown in FIG. 2, an image forming apparatus which is one example of the image reader according to the present invention has an original table 2 comprising a transparent glass or the like on the upper face of the main body 1. Under the original table 2, a scanner section 3 which is an optical

device is arranged.

As the scanning method of the optical device, in this embodiment, a scanning method using an image sensor (for example, CCD (Charge Coupled Device), PDA (Photo Diode Array) and the like) using a light source consisting of a plurality of lamp array will be described. However, the shape of the light source (for example, fluorescent light lamp, halogen lamp, flash lamp and the like as a linear light source) and the scanning method are not limited at all, and any shape of the light source and any scanning method may be used so far as the quantity of irradiation light is changed with lapse of time as the moving documents are continuously read.

The scanner section 3 in this embodiment comprises a light source 3a for irradiating light to a document put on the original table 2, a plurality of reflection mirrors 3d for guiding the reflected light from the document to a photoelectric conversion element (CCD) 3c arranged in the direction of light transmission (toward right in FIG. 2) through an imaging lens 3b in the scanner section 3, as shown in a chain line in the drawing, the aforesaid imaging lens 3b arranged in the optical path and the aforesaid CCD 3c.

The image data of the document read by the CCD 3c is subjected to image processing in an image processing section described later, and sent to a laser scanning unit (hereinafter referred to as LSU) 4 in an image forming section 10, and the

LSU 4 irradiates laser beam to the surface of a photosensitive member 5 to form an electrostatic latent image on the surface of the photosensitive member 5.

5 The photosensitive member 5 is in a drum shape rotated and driven in the direction of an arrow. In the periphery of this photosensitive member 5, there are provided in the order of from a laser irradiation point toward the rotation direction of the photosensitive member 5, a development apparatus 6 for developing the electrostatic latent image on the surface of the photosensitive member exposed by the laser into a visual
10 image by the toner, a transfer charger 7 for transferring the toner image on the photosensitive member 5 onto a paper, a cleaning device 8 for removing the residual toner on the surface of the photosensitive member 5, a main charger 9 for charging
15 the photosensitive member to the predetermined electric potential, and LSU 4 for irradiating laser beam toward the laser irradiation point on the photosensitive member 5.

The transfer paper is stored in a paper cassette 11a in a paper feed section 11.

20 A semicircular roller 12 for feeding papers is provided on the upper part of the tip on the feeding side of the paper cassette 11a, and the transfer paper P pressed by the semicircular roller 12 is fed with the rotation of the semicircular roller 12. Moreover, in the image forming
25 section 10, there are arranged, toward the downstream side in

the carrying direction of the transfer paper P (for convenience sake, feeding side of the transfer paper P (cassette side) is designated as the upstream side and the paper ejection side is designated as the downstream side), a resist pre-detection switch (not shown) for detecting the passage of the transfer paper P, a resist roller 13 for performing the position adjustment of the toner image on the photosensitive member 5 and the transfer paper based on the signal from the resist pre-detection switch, a transfer charger 7 for transferring the toner image on the photosensitive member onto the transfer paper P, an upper fixing roller 14 and a lower fixing roller 15 for fixing the toner image on the transfer paper by means of heat, a fixed paper detection switch SW1 for detecting that the transfer paper passes the fixing rollers 14 and 15, an ejection paper detection switch SW2 for detecting that the transfer paper passes before a paper ejection roller 16, and the aforesaid paper ejection roller 16 for ejecting the transfer paper.

Furthermore, a manual feed tray 17 is provided on the back side of the body 1, and depending upon the user's request, after the transfer paper has been inserted from the manual feed tray 17 to the aforesaid resist roller 13, the printing process is performed by means of the rotation of the resist roller 13 for performing the position adjustment of the toner image on the photosensitive member 5 and the transfer paper.

The printed transfer paper is ejected to the space adjacent to the image forming section 10, and between the upper part of the paper cassette 11 and the lower part of the scanner section 3.

5 In the case of a copying machine (including analogue and digital), in general, there is the one in which an image can be taken in a bigger size than the transfer paper. For example, the size of the image taken in the scanner section 3 is at maximum A3 or B4, and the transfer paper is at maximum
10 A4 size. The size taken in the scanner section 3 is reduced and copied. In this case, among the scanner section 3, the image forming section 10 and the paper feed section (cassette section) 11, the one which requires the biggest area as the machine structure is the scanner section 3. Since it is
15 necessary to take a document in a big size, it requires inevitably a big area. The image forming apparatus in FIG. 2 has such a construction.

Next is a description of the characteristic part of the present invention with reference to FIG. 3 to FIG. 8.

20 With the above described image forming apparatus 1, the second standard white boards B and C are provided in positions which are not used for actual document read, at the end portion in the main scanning direction (MS) of the position P2 for reading the moving document (FIG. 4) in the document moving mode.
25 By reading the second standard white boards B, C together with

the document at the time of reading the document to thereby correct the quantity of light of the light source, even in the document moving mode, readout of the document with adequate quantity of light becomes possible, and accurate shading correction can be performed.

FIG. 3 is a sectional view of the scanner section 3, and FIG. 4 is a top view of the scanner section 3. The scanner section 3 is provided with a document fixing-type platen glass 2a on which the document is put in the document fixing mode, and a document moving-type platen glass 2b for reading the moving document carried by the document automatic feeder 30 arranged on the upper part of the body 1 in the document moving mode.

In the region on the one end side of the platen glass 2a in the sub scanning direction (SS) used in the document fixing method (FIG. 4), a belt-form first standard white board A whose whole length Y is the length extended from the width of the platen glass 2a in the main scanning direction towards both end sides by a predetermined width is arranged. Hereinafter, the position where the first standard white board A is arranged is referred to as a "home position P1".

On both sides in the main scanning direction of the document passing area X of the document moving type platen glass 2b used for reading the document which uses the document automatic feeder 30, rectangular second standard white boards

B and C are provided in prescribed locations, and the length in the main scanning direction (in the right-angled direction to the moving direction of the document) from the second standard white board B via the document passing area X to the second standard white board C is the same with the length Y of the first standard white board A. Here, the document putting (passing) area shown by a symbol X in FIG. 4 (hereinafter may be referred to as "document occupancy area") is the maximum size of the document which can be read by the scanner section 3.

The size of the platen glasses 2a and 2b in the main scanning direction of the document fixing method and the document moving method is formed larger than the document occupancy area X, and the size of the light source 3a consisting of a plurality of lamp arrays in the longitudinal direction (the main scanning direction) is also formed larger than the document occupancy area X. Moreover, the document readout area Y where the CCD 3c can read the reflected light irradiated from the light source 3a in the document moving method is also formed longer than the document occupancy area X in the main scanning direction. Therefore, the readable area of the CCD 3c and the area between the both ends of the first standard white board A and the second standard white boards B, C are the same, hence read in of the first standard white board A and the second standard white boards B, C becomes possible.

FIG. 5A shows the light distribution characteristic of the light source lamp at the time of read in in the main scanning direction, and shows that the peak quantity of light is after and before a predetermined time (distance) at the time of start and end of irradiation of the lamp, and the quantity of light becomes stable between the peak period.

Therefore, the light source 3a for reading the document is so set that the area of a symbol X_2 in FIG. 5A, that is, an area where the quantity of light of the light source 3a is uniform becomes the document occupancy area X used for the actual read of the document. In this drawing, a symbol Y_2 shows an irradiation period of the lamp between both ends of the first standard white board A and the second standard white boards B and C, a symbol B_2 shows the irradiation period of the second standard white board B and a symbol C_2 shows the irradiation period of the second standard white board C, respectively.

FIG. 6 is a block diagram of a control system of the above described image forming apparatus 1. To the control section 40 comprising CPU (Central Processing Unit) and the like are connected an image information processing section 41 for performing predetermined image processing to the image data and a printing processing section (image forming section) 42 for performing printing based on the image data processed in the image information processing section 41, as well as a light source unit drive control section 43, a light source lamp

voltage control section 44, a shading correction section 45 and a plurality of memories 46, 47 and the like.

The light source unit drive control section 43 is for controlling the drive of the light source unit comprising the light source 3a and mirrors 3b of the scanner section 3, and the light source lamp voltage control section 44 is for controlling the applied voltage which determines the quantity of light of the light source 3a.

The shading correction section 45 controls the light source unit drive control section 43 via the control section 40 to perform the above described shading correction.

The operation at the time of reading the document will be described based on the flowchart, in both the document moving/document fixing modes in the image forming apparatus 1 having the construction described above.

First, the reading operation in the document fixing mode will be described with reference to the flowchart in FIG. 7 and FIGs. 3 and 4.

When a document is put on the platen glass (original table) 2a of the image forming apparatus 1, and a not-shown start button is pushed, readout is started. When a document read request is received (S1), the light source 3a for reading documents is first returned to the home position P1 before reading the document (S2, S3).

Next, irradiate light to the first standard white board

A arranged at the end portion of the platen glass 2a by means of the light source 3a returned to the home position P1, to read the reflected light of the first standard white board A by means of the CCD 3c via the mirrors 3d in the optical path and the lens 3b (S4).

Then, based on the quantity of reflected light of the first standard white board A read by the CCD 3c, perform the shading correction for correcting the difference in sensitivity for each pixel of the read sensor (CCD) and the nonuniformity in the quantity of light of the light source 3a, to thereby determine the threshold of the white/black judgement at the time of reading the document for each pixel (S5).

Thereafter, carry out the document read by scanning of the light source unit 3 in the document putting area for reading the document (S6), and if there is another document to be read, return to the step S2, and continue the above operation.

In such a document fixing mode, even at the time of continuous read, the shading correction for each pixel to be read is carried out for each document, hence the threshold of the white/black judgement for each pixel does not shift.

Next is a description of the document read operation in the document moving mode with reference to the flowchart in FIG. 8 and FIGs. 3 and 4. A document is put on the document feed tray 30a in the document automatic feeder 30 shown in FIG. 3, and when the start button is pushed, the document is fed

from the topmost layer by a pickup roller 30b, and carried through a carrier path 30c to the moving document read section by a resist roller 30d at a timing synchronous to the read timing. The read document is stored in a document ejection tray 30f by means of a carrier roller 30e in the carrier path 30c, and read of the next document is performed in the similar manner.

Here, when the start button (not shown) is pushed, readout is stated. As in the document fixing mode, when a document read request is received (S11), the light source 3a for reading documents is first returned to the home position P1 before reading the document (S12, S13).

Next, irradiate light to the first standard white board A arranged at the end portion of the platen glass 2a by means of the light source 3a returned to the home position P1, to read the reflected light of the first standard white board A by means of the CCD 3c via the mirrors 3d in the optical path and the lens 3b (S14).

Then, based on the quantity of reflected light of the first standard white board A read by the CCD 3c, perform the shading correction for correcting the difference in sensitivity for each pixel to be read by the read sensor (CCD 3c) and the nonuniformity in the quantity of light of the light source 3a, to thereby determine the threshold of the white/black judgement at the time of reading the document for each pixel (S15). At this time, at least the data such as

applied voltage to the light source 3a after the shading correction between the portions B₂ and C₂ shown in FIG. 5A and the like is stored in the memory 46 (see FIG. 6).

Thereafter, move the light source 3a (optical system) in the sub scanning direction, and after the light source 3a has reached the moving document read section (downward of the platen glass 2b) P2 in the document moving mode (S16), carry the document to the moving document read section P2 (S17) to carry out the document read. Then, at the same time, read the reflected light of the second standard white boards B, C located at both ends in the longitudinal direction (in the main scanning direction) of the light source 3a by the CCD 3c (S18).

The light source 3a for reading documents has the light distribution characteristic as shown in FIG. 5A, and when documents are read continuously, since the lamp temperature increases, the quantity of light decreases as a whole as shown in FIG. 5B.

Therefore, in the step (S19), the data of quantity of light of the second standard white boards B and C read in the step (S18) is stored in the memory 47, as well as said data and the initial data of quantity of light using the first standard white board A which is stored in the memory 46 are compared in the control section 40. When there is a difference between those data, the light source lamp voltage control section 44 is controlled in the step (S20) to thereby adjust

the voltage applied to the light source 3a, and the quantity of light is corrected so that the irradiation quantity to the second standard white boards B, C and the irradiation quantity to the first standard white board A become the same (see FIG. 5).

If the decrease in the quantity of light is not confirmed after the correction or in the step (S19), proceed to the step (S21), and if there is the next document to be read, return to the step (S17), and perform correction so that only the quantity of light of the whole area of the lamp in the light source 3a is changed to the initial quantity of light when the shading correction was performed in the step (S14).

By providing the processes as described above, even if in the document moving mode, the shading correction using the first standard white board A can only be performed to the first document by the light source unit located in the home position P1, the quantity of light of the light source 3a is monitored with respect to the document to be read thereafter, and when the quantity of irradiation light changes due to the change of the temperature of the light source with lapse of time, it can be corrected so as to maintain the initial quantity of light by adjusting the control voltage applied to the light source 3a. Hence, the threshold of the white/black judgement determined by the shading correction does not shift, without reducing the read rate or without requiring complicated control,

and high quality of reproduced document can be obtained.

In the above described embodiment, a preferable example of the present invention has been described, but it is a matter of course that the present invention is not limited thereto.

5 For example, in the above embodiment, correction of quantity of light is performed for every document by using the second standard white boards B and C. However, the correction timing of the quantity of light can be optionally selected, and optimum timing (number of documents) can be selected depending upon
10 the readout quantity of continuous documents and the change in the quantity of irradiation light of the light source 3a.

Furthermore, in the above embodiment, the reflected light is determined at two positions of the second standard white boards B and C for performing correction of the quantity
15 of light more reliably, but it is a matter of course that only one of them may be used.

As described above, according to the invention of the first or second gist, at the time of document moving mode, the control section performs shading correction based on the
20 quantity of reflected light of the first standard white board arranged wider than the whole width of the document passing area or of the document read area in the main scanning direction, for example, corrects the difference in sensitivity between pixels of the readout section and the nonuniformity in the
25 quantity of light of the light source, immediately before

starting read in of the moving document.

After performing the shading correction to thereby make the readout section the optimum state, the control section moves the readout section to a position where the moving document can be read, and read the quantity of reflected light of the second standard white board provided in a prescribed location at an end portion in the main scanning direction where the document does not pass through, every time predetermined moving documents are read, and based on the result, the control section detects the change in the quantity of irradiation light of the readout section, and corrects the quantity of irradiation light of the readout light source.

Therefore, even if the quantity of irradiation light of the readout section decreases due to the continuous readout of the documents in the document moving mode, the quantity of irradiation light is maintained in the quantity of irradiation light after the shading correction performed by using the first standard white board, every time predetermined documents are read. Hence, the threshold of the white/black judgement determined by the shading correction does not shift, without reducing the read rate or without requiring complicated control, and high quality of reproduced document can be obtained.

According to the invention of the third gist, by arranging the second standard white board at both ends rather than at one end portion in the main scanning direction, more

accurate correction of the quantity of light can be performed.

According to the invention of the fourth gist, in the document moving mode, the change in the quantity of light of the readout light source with lapse of time can be detected by providing the standard white board in a prescribed location in the external region of the end portion by utilizing the external region of the end portion in the main scanning direction in the area where the moving document does not pass through, and by reading the reflected light from this standard white board together with the reflected light from the moving document. Hence, it becomes possible to correct the quantity of light of the readout light source to the predetermined quantity of light based on the change in the quantity of light.

Therefore, even in the document moving mode, correction of quantity of light becomes possible every time a document is read, without reducing the read rate and without requiring complicated control, and thus, the change in the quantity of light due to the change with lapse of time of the light source at the time of continuous readout can be properly corrected.

According to the invention of the fifth gist, in the document moving mode, for example, shading correction of nonuniformity in the quantity of light, difference in sensitivity of the pixel portion to be read is performed based on the reflected light of the first standard white board immediately before initiating readout of the document. Then,

the light source moves to the read position where the moving document is read, and the moving documents are continuously read to cause a change in the quantity of light due to the temperature increase of the light source. However, the change in the quantity of light of the readout light source can be detected and the change thereof with lapse of time can be corrected by reading the reflected light which is irradiated by using the light source and reflected from the second standard white board provided in the region where the document does not pass through, for example, in the external region of the end portion in the main scanning direction of the passing document, every time predetermined documents are read.

Therefore, in the document moving mode, the change in the quantity of light of the light source can be corrected, while performing continuous read of documents, and the quantity of light of the document can be maintained in the quantity of light corrected by using the first standard white board. Hence, the threshold of the white/black judgement determined by the shading correction by using the first standard white board can be maintained, without interrupting continuous read for performing the shading correction, reducing the read rate or requiring complicated control, and high quality of reproduced document can be obtained.

WHAT IS CLAIMED IS

1. An image reader having a document moving mode in which an original document carried through a document passing area on an original table is read by a readout section, characterized in that:

a first standard white board being longer than the length of said document passing area with respect to the main scanning direction is provided outside the document passing area;

a second standard white board is provided in an external region of an end portion of the document passing area with respect to the main scanning direction;

a control section controls the readout section in such a way that, in the document moving mode, the readout section reads the first standard white board prior to the initiation of the document read to thereby perform the shading correction, and after the document read has been initiated, said readout section reads the moving document as well as the reflected light of the second standard white board, so as to correct the quantity of irradiation light of said readout section, based on the reflected light from said second standard white board.

2. An image reader having both of a document fixing mode in which a readout section moves to read an original document put in a document putting area on an original table and a document moving mode in which the original document carried

through a document passing area on the original table is read by the readout section, characterized in that:

5 a first standard white board being longer than the length of said document putting area with respect to the main scanning direction is provided outside the document putting area;

a second standard white board is provided in an external region of an end portion of the document passing area with respect to the main scanning direction;

10 a control section controls the readout section in such a way that, in the document moving mode, the readout section reads the first standard white board prior to the initiation of the document read to thereby perform the shading correction, and after the document read has been initiated, said readout
15 section reads the moving document as well as the reflected light of the second standard white board, so as to correct the quantity of irradiation light of said readout section, based on the reflected light from said second standard white board.

20 3. An image reader according to claim 1 or 2, wherein said second standard white board is provided in the external region of both end portions of the document passing area with respect to the main scanning direction .

25 4. A method for correcting the quantity of light of a readout light source used in an image reader which irradiates

an original document with the readout light source and reads the original document image based on the reflected light thereof, wherein

5 in a document moving mode in which the original document moves, the moving document image is read by using said readout light source, and the reflected light from a standard white board arranged outside a document passing area is also read; and

10 correction of the quantity of irradiation light of said readout light source is performed based on the reflected light from said standard white board.

5. A method for correcting the quantity of light of a readout light source used in an image reader which irradiates an original document with the readout light source and reads
15 the original document image based on the reflected light thereof, wherein

in a document moving mode in which the document moves, correction of the quantity of irradiation light of the readout light source is performed by reading a first standard
20 white board which is longer than the length in the main scanning direction of a document passing area, prior to the initiation of the document read;

upon initiation of readout of the moving document, both the document and a second standard white board arranged outside
25 the document passing area are read, by using said readout light

source; and

correction of the quantity of irradiation light of said readout light source is performed based on the reflected light from said second standard white board.

ABSTRACT OF THE DISCLOSURE

In the correction of the quantity of light of a light source used in an image reader which irradiates an original document with the light source, receives the reflected light by a CCD and reads the original document image, at the time of a document moving mode in which the document moves, correction of the quantity of irradiation light of the light source is performed by reading a first standard white board which extends over the whole area in the main scanning direction, prior to the initiation of readout of the moving document, and upon initiation of readout of the moving document, a second standard white board arranged outside the document passing area is read by using the same light source, with the read operation of the moving document, and correction of the quantity of irradiation light of the light source is performed based on the reflected light from the second white board.

FIG. 1 PRIOR ART




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7





FIG. 8



PATENT (US)

Attorney Docket No. _____

COMBINED DECLARATION AND POWER OF ATTORNEY
(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Title: IMAGE READER AND METHOD FOR CORRECTING THE QUANTITY OF LIGHT OF THE READOUT LIGHT SOURCE

the specification of which

(a) ☒ is attached hereto.

(b) _____ was filed on _____ as _____ Serial No. 0 / _____ or _____ Express Mail No. _____, as Serial No. not yet known, and was amended on _____ (if applicable).

(c) _____ was described and claimed in PCT International Application No. _____ filed on _____ and amended under PCT Article 19 on _____ (if any).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations §1.56(a).

PRIORITY CLAIM

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

(d) _____ no such application have been filed.

(e) ☒ such applications have been filed as follows.

**EARLIEST FOREIGN APPLICATION(S), IF ANY FILED WITHIN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION**

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119
<u>Japan</u>	<u>Hei 11-068978</u>	<u>15/Mar./1999</u>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No

**ALL FOREIGN APPLICATION(S), IF ANY FILED MORE THAN 12 MONTHS
(6 MONTHS FOR DESIGN) PRIOR TO THIS U.S. APPLICATION**

CLAIM FOR BENEFIT OF EARLIER U.S./PCT APPLICATION(S) UNDER 35 U.S.C. 120

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

**PRIOR U.S. OR PCT APPLICATIONS
DESIGNATING THE U.S. FOR BENEFIT UNDER 35 USC 120**

APPLICATION NO.	U.S. FILING DATE (day month, year)	STATUS (Patented, Pending, Abandoned)
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

D-US-1.FRM

POWER OF ATTORNEY

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

Armand P. Boisselle, Reg. No. 22,381

Neil A. DuChez, Reg. No. 26,725;

Mark D. Saralino, Reg. No. 34,243

Gregory Turocy, Reg. No. 36,952

The undersigned to this declaration and power of attorney hereby authorizes the U.S. attorney(s) named herein to accept and follow instruction from

Name(s) of authorized representation(s) Fujimoto Patent and Law Office

Address Room 317, Sanno Grand Building, 14-2, Nagata-cho 2-Chome, Chiyoda-Ku, Tokyo 100-0014, Japan

as to any actions to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney(s) and the undersigned. In the event of a change in the person(s) from whom instructions may be take, the U.S. attorney(s) will be so notified by the undersigned.

Send Correspondence To

Neil A. DuChez
RENNER, OTTO, BOISSELLE & SKLAR, P.L.L.
1621 Euclid Avenue, 19th Floor
Cleveland, Ohio 44115

Direct Telephone Calls To:
(name and telephone number)

Neil A. DuChez
(216) 621-1113

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued therein.

D-US-1.FRM

70-00387-15 - 6 - 117)

[illegible]

X Signature for third and subsequent joint inventors. Number of pages added 1.

_____ This declaration ends with this page.

92-111)

20 7 2 7 6

**ADDED PAGE TO COMBINED DECLARATION AND POWER OF ATTORNEY
FOR SIGNATURE BY THIRD AND SUBSEQUENT INVENTORS**

Full name of third joint inventor Michiaki NISHIMURA
Inventor's signature Michiaki Nishimura
Date Feb. 9, 2000 Country of Citizenship Japan
Residence Yoshino-gun, Nara, Japan
Post Office Address 565, Haradani, Shimoichi-cho, Yoshino-gun, Nara, Japan

Full name of fourth joint inventor, if any Kazuya MASUDA
Inventor's signature Kazuya Masuda
Date Feb. 9, 2000 Country of Citizenship Japan
Residence Nara-shi, Nara, Japan
Post Office Address 3-6-19, Rokujonishi, Nara-shi, Nara, Japan

Full name of fifth joint inventor, if any Noritomo NAKASHIMA
Inventor's signature Noritomo Nakashima
Date Feb. 9, 2000 Country of Citizenship Japan
Residence Yamatokorivama-shi, Nara, Japan
Post Office Address Yamato-ryo Nishi-kan 434, 492, Minosho-cho, Yamatokoriyama-shi, Nara, Japan


Full name of sixth joint inventor, if any Takehiro KATO
Inventor's signature Takehiro Kato
Date Feb. 9, 2000 Country of Citizenship Japan
Residence Yamatokoriyama-shi, Nara, Japan
Post Office Address Yomato-ryo Nishi-kan 429, 492, Minosho-cho, Yamatokoriyama-shi, Nara, Japan

CERTIFICATION UNDER 37 CFR 1.10

I hereby certify that the attached patent application (along with any other paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on this date **February 23, 2000**, in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number **EJ887878374US** addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231.

Janet Farr

Typed or Printed Name of Person Mailing Paper


(Signature of Person Mailing Paper)